

Parking Lot Restriping at Collierville Schools

Scope of Work

Prepare all surfaces for the application of paint in accordance with manufacturer's recommendations. Clean lots as needed to ensure adequate paint adhesion. Restripe parking lots as previously marked, unless noted otherwise by Collierville Schools. Paint parking stalls, handicap space symbols, "Stop" stencils w/ bars, directional arrows, lane dividers, crosswalk hatching, fire lane hatching, "Fire Lane" stencils, "No Parking" stencils, and repaint fire lane curbs.

Locations

Bailey Station Elementary – 3435 Bailey Station Road, Collierville, TN 38017

Collierville Elementary – 590 Peterson Lake Road, Collierville, TN 38017

Collierville High – 1101 New Byhalia Road, Collierville, TN 38017

Collierville Middle – 580 Quinn Road, Collierville, TN 38017

Crosswind Elementary – 831 Shelton Road, Collierville, TN 38017

Schilling Farms Middle – 935 Colbert Street South, Collierville, TN 38017

Sycamore Elementary – 1155 Sycamore Road, Collierville, TN 38017

Tara Oaks Elementary – 600 E. Harpers Ferry, Collierville, TN 38017

Quantity and Schedule

Parking lots will be restriped between May 31, 2016 and June 30, 2017. Locations and schedules will be determined by Collierville Schools and will be based upon priority. The quantity of parking lots to be completed will be based on available funding.

Specifications

PART 1 PRODUCTS

A. Line and Zone Marking Paint: Sherwin Williams Pro-Park Waterborne Traffic Marking Paint, or equivalent (MPI No. 97 Latex Traffic Marking Paint). Colors as indicated.

1. Parking Spaces: White
2. Handicapped Symbols: Blue
3. All other markings: Match existing, unless noted otherwise by Collierville Schools

PART 2 PREPARATION

A. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

B. Clean surfaces thoroughly prior to installation:

1. Remove dust, dirt, and other granular surface deposits by sweeping, blowing with compressed air, rinsing with water, or a combination of these methods.
2. Where oil or grease are present, scrub affected areas with tri-sodium phosphate and rinse thoroughly. After cleaning, seal the affected areas with cut shellac to prevent bleed through.

- C. Use templates to control paint application as needed.

PART 3 INSTALLATION

- A. Apply in accordance with manufacturer's instructions using an experienced technician that is thoroughly familiar with the equipment, materials, and marking layouts.
- B. Apply uniform painted markings of color, lengths, and widths with true sharp edges and ends.
 - 1. Apply paint in one coat only
 - 2. Wet Film Thickness: 0.015 inch, minimum
 - 3. Width Tolerance: 4" plus or minus 1/8".
- C. Do not apply paint if temperatures of the surface or the atmosphere are less than 50 degrees F or greater than 95 degrees F.
- D. Do not apply paint if wind speeds are sufficient to cause overspray.

PRICING SHEET

Please provide unit pricing in the spaces indicated below. Pricing should be based on the specifications and should include all labor, equipment, and materials. Pricing shall be valid until June 30, 2017.

ITEM	UNIT	UNIT PRICE
Parking Spaces	LF	
Handicapped Symbols	EA	
"STOP" Stencils w/ Stop Bar	EA	
"NO PARKING" Stencils	EA	
"FIRE LANE" Stencils	EA	
Hatching	LF	
Fire Lane Curb	LF	
Directional Arrows	EA	
Lane Divider	LF	
Street Sweeper (if needed)	Per Hour	

Total Bid Price for all Items \$ _____

Percent (%) of discount if awarded All Projects _____%

State your cost per \$1,000.00 for Performance, Materials and Labor Bond, if required \$ _____

Company Name